

For the production of wood pellets produced by

Kurzemes Granulas SIA, Ventspils, LATVIA

certified according to **ENplus® A1 and A2** with the ID number: **LV002**

we confirm the following test results analysed within the inspection 2019 valid until the inspection in 2020.

Samples 2019342	Standard	unit	Pellets class A1	Pellets class A2	Limit values according ENplus®		Limit values according DINplus
					Class A1	Class A2	
mechanical durability**	ISO 17831-1	[%]	98,6	97,6	≥ 98,0	≥ 97,5	≥ 97,5
bulk density (ar)**	ISO 17828	[kg/m³]	670	690	750≥BD≥600	750≥BD≥600	750≥BD≥600
moisture content**	ISO 18134-2	[%]	6,2	5,4	≤ 10	≤ 10	≤ 10
ash content 550°C(db)**	ISO 18122	[%]	0,4	0,5	≤ 0,7	≤ 1,2	≤ 0,7
net calorific value (ar)**	ISO 18125	[MJ/kg]	17,6	17,9	≥ 16,5	≥ 16,5	≥ 16,5
net calorific value (ar)**	ISO 18125	[kWh/kg]	4,9	5,0	≥ 4,6	≥ 4,6	≥ 4,6
net calorific value (db)**	ISO 18125	[MJ/kg]	19,0	19,0	-	-	-
net calorific value (db)**	ISO 18125	[kWh/kg]	5,3	5,3	-	-	-
gross calorific value (ar)**	ISO 18125	[MJ/kg]	19,0	19,3	-	-	-
gross calorific value (ar)**	ISO 18125	[kWh/kg]	5,3	5,4	-	-	-
Sulphur content (db)	ISO 16994	[%]	0,007	0,009	≤ 0,04	≤ 0,05	≤ 0,04
Chlorine content (db)	ISO 16994	[%]	0,006	0,005	≤ 0,02	≤ 0,02	≤ 0,02
Nitrogen content (db)	ISO 16948	[%]	0,05	0,07	≤ 0,30	≤ 0,50	≤ 0,30
pressing aid / additives	-	[%]	0,7	0	≤ 2	≤ 2	≤ 2
dimensions**							
finer (< 3,15 mm)	ISO 18846	[%]	0,2	0,2	≤ 0,5* / ≤ 1	≤ 0,5* / ≤ 1	≤ 0,5* / ≤ 1
length (3,15 ≤ L ≤ 40 mm)	ISO 17829	[%]	99,8	99,8	> 98,5* / > 98	> 98,5* / > 98	> 98,5* / > 98
length (40 ≤ L ≤ 45 mm)	ISO 17829	[%]	0	0	≤ 1	≤ 1	≤ 1
length (> 45 mm)	ISO 17829	[amount]	0	0	0	0	0
diameter	ISO 17829	[mm]	6	6	6 or 8 ± 1	6 or 8 ± 1	6 or 8 ± 1
heavy metals***							
Chromium (db)	ISO 16968	[mg/kg]	< 1	< 1	≤ 10	≤ 10	≤ 10
Copper (db)	ISO 16968	[mg/kg]	2,1	1,4	≤ 10	≤ 10	≤ 10
Zinc (db)	ISO 16968	[mg/kg]	9,7	14,0	≤ 100	≤ 100	≤ 100
Lead (db)	ISO 16968	[mg/kg]	< 0,5	< 0,5	≤ 10	≤ 10	≤ 10
Mercury (db)	ISO 16968	[mg/kg]	< 0,075	< 0,075	≤ 0,1	≤ 0,1	≤ 0,1
Cadmium (db)	ISO 16968	[mg/kg]	< 0,1	0,13	≤ 0,5	≤ 0,5	≤ 0,5
Arsenic (db)	ISO 16968	[mg/kg]	< 0,1	< 0,1	≤ 1	≤ 1	≤ 1
Nickel (db)	ISO 16968	[mg/kg]	< 1	< 1	≤ 10	≤ 10	≤ 10
ash melting behaviour (ash preparation at 815°C)**							
shrinking temperature SST	CEN/TS 15370-1	[°C]	1200	1280	-	-	-
deformation temperature DT	CEN/TS 15370-1	[°C]	1510	> 1600	≥ 1200	≥ 1100	≥ 1200
hemisphere temperature HT	CEN/TS 15370-1	[°C]	> 1600	> 1600	-	-	-
flow temperature FT	CEN/TS 15370-1	[°C]	> 1600	> 1600	-	-	-

* for bags or sealed big bags, ar...as received, db...dry basis